



NOTES:

1. BROOM FINISH CONCRETE, UNLESS DIRECTED OTHERWISE BY THE PUBLIC WORKS INSPECTOR.
2. SAW CUT EXISTING SIDEWALK TO THE NEAREST SCORE LINES.
3. TOOL SCORE LINES AS DIRECTED BY THE PUBLIC WORKS INSPECTOR.
4. PROVIDE EXPANSION JOINTS (FELT) AT 30 FT. (MAXIMUM) SPACING, WIDTH NOT TO EXCEED 3/8"
5. PROVIDE ONE IN. DEEP CONTROL JOINTS AT 8 FT. (MAXIMUM) SPACING; MATCH EXISTING SCORELINES
6. CONCRETE MIX SHALL CONSIST OF: 3/4 IN. AGGREGATE, 5 SACK, TYPE 2, PORTLAND CEMENT. PROVIDE ONE POUND LAMP BLACK PER CUBIC YARD CONCRETE.
7. THE CONTRACTOR IS RESPONSIBLE FOR CORRECTING CONCRETE DEFACED BY GRAFITTI UNTIL THE WORK IS ACCEPTED BY THE PUBLIC WORKS INSPECTOR.

No	By	Revision	Date
1	SDC	3/8" width, R=1"	3/2011

CITY OF SAN PABLO

ONE ALVARADO SQUARE, SAN PABLO, CA 94806
 (510) 215-3030 FAX 215-3031



CITY OF SAN PABLO
 City of New Directions

Checked By: _____

Approved By: _____

PUBLIC WORKS DIVISION MANAGER _____ DATE _____

SIDEWALK AND CURB AND GUTTER
 PLAN, SECTION, NOTES
 (FOR REPAIRS AND NEW WORK)
 NO SCALE

STD DET SA-03

SHEET 1 OF 1